

Super synth

SAE 0W-40. 5W- 40. 5W- 50. 10W- 40

Description:

Kompressol-Super Synth is a newly developed, synthetic low-friction motor oil, which was formulated according to the latest technology. Together with an extremely powerful additive system, the highest requirements of modern motor oil technology are exceeded.

Kompressol-Super Synth offers as high-performance engine oil of the high-tech class:

- ideal cold start ability
- absolutely reliable lubricity in all temperature and load conditions
- excellent engine cleanliness
- Prevention of sludge formation
- optimal wear protection
- Fuel saving
- Unrestricted catalytic converter and turbo suitability

Kompressol-Super Synth can be used as a year-round oil in all passenger car gasoline engines, diesel engines and turbo engines.

Mixing with other non-synthetic or semi-synthetic motor oils is permitted. However, the outstanding properties of Kompressol-Super Synth are largely lost when mixed with foreign oils.

Shortened flushing intervals are not required when lubricating engines with the Kompressol-Super Synth.

Kompressol-Super Synth is suitable for vehicles with diesel particle filters (observe manufacturer's instructions).

Specifications:

ACEA	A3 / B4
API	SN

Recommendations:

BMW	Longlife 01
Chrysler	MS-12633 (0W-40) MS-10725 (0W-40)
Fiat	9.55535-H2 / N2 / Z2 9.55535-M2 (0W-40 / 5W40)
ford	WSS-M2C937-A (0W-40)
MB	226.5, 229.1, 229.3, 229.5
Opel	GM-LL-B-025
Porsche	A 40
P.SA	B71-2296, B71-2300 B71-2300 (SAE 10W-40)
Renault	RN 0700, RN 0710
VW standard	502.00 / 505.00 / 505.01

Status: 03/2021

Application: